



- 1, Tolerance of running accuracy are according to relevant state standard;
- 2, The value of the basic group of radial clearance: min 0.035 max 0.055 ;
- 3, Rated load: Cr=129 kN Cor=130 kN.

62	Guide ring	1	Steel 20—GB/T699		
07	Cage	2	Brass CuZn39Pb2—EN 1652:1997		
04	Roller		Steel 100CrMnSi6—4—ISO 683-17:1999		
02	Inner ring	1	Steel 100CrMnSi6—4—ISO 683-17:1999		
01	Outer ring	1	Steel 100CrMnSi6—4—ISO 683-17:1999		

No.	Designation	Qty	Material	unit	total	Remark
				Weight (kg)		

<p>Luoyang JCB Bearing Technology Co., Ltd                  Contact information                  Company Address : No. 285, Fenghua road,                  Luoyang, Henan, China.                  Postal code : 471000                  Phone :86-379-68611678                  Fax : 86-379-68611679                  E-mail: sales@jcb-bearing.com                  Reserved E-mail: sales@sphericalrollerbearing.net                  Website: www.jcb-bearing.com                  www.sphericalrollerbearing.net</p>	<h2>Spherical Roller Bearing</h2>		21309-E1-XL			
					Weight(kg)	Scale
			S		0.845	—
			Total page 5		Page No. 1	
Luoyang JCB Bearing Technology Co., Ltd						