



1. Tolerance of running accuracy are according to relevant state standard;
2. The value of the basic group of radial clearance: min 0.035 max 0.055 ;
3. Rated load: Cr=187 kN Cor=183 kN.

|    |            |   |                                    |  |  |
|----|------------|---|------------------------------------|--|--|
| 62 | Guide ring | 1 | Steel 20—GB/T699                   |  |  |
| 07 | Cage       | 2 | Brass CuZn39Pb2—EN 1652:1997       |  |  |
| 04 | Roller     |   | Steel 100CrMnSi6-4—ISO 683-17:1999 |  |  |
| 02 | Inner ring | 1 | Steel 100CrMnSi6-4—ISO 683-17:1999 |  |  |
| 01 | Outer ring | 1 | Steel 100CrMnSi6-4—ISO 683-17:1999 |  |  |

| No. | Designation | Qty | Material | unit        | toatl | Remark |
|-----|-------------|-----|----------|-------------|-------|--------|
|     |             |     |          | Weight (kg) |       |        |

|   |                                   |              |            |            |
|---|-----------------------------------|--------------|------------|------------|
| <p>Luoyang JCB Bearing Technology Co., Ltd</p> <p>Contact information</p> <p>Company Address : No. 285, Fenghua road, Luoyang, Henan, China.</p> <p>Postal code : 471000</p> <p>Phone :86-379-68611678</p> <p>Fax : 86-379-68611679</p> <p>E-mail: sales@jcb-bearing.com</p> <p>Reserved E-mail: sales@sphericalrollerbearing.net</p> <p>Website: www.jcb-bearing.com</p> <p>www.sphericalrollerbearing.net</p> | <h2>Spherical Roller Bearing</h2> | 22309-E1-XL  |            |            |
|   |                                   |              | Weight(kg) | Scale      |
|   |                                   | S            | 1.39       | —          |
|   |                                   | Total page 5 |            | Page No. 1 |
| Luoyang JCB Bearing Technology Co., Ltd   |                                   |              |            |            |