



- 1、Tolerance of running accuracy are according to relevant state standard;
- 2、The value of the basic group of radial clearance:min 0.035 max 0.055 ;
- 3、Rated load: Cr=229 kN Cor=223 kN.

62	Guide ring	1	Steel 20—GB/T699			
07	Cage	2	Brass CuZn39Pb2-EN 1652:1997			
04	Roller		Steel 100CrMnSi6-4—ISO 683-17:1999			
02	Inner ring	1	Steel 100CrMnSi6-4—ISO 683-17:1999			
01	Outer ring	1	Steel 100CrMnSi6-4—ISO 683-17:1999			

No.	Designation	Qty	Material	unit	total	Remark
				Weight (kg)		

<p>Luoyang JCB Bearing Technology Co., Ltd</p> <p>Contact information</p> <p>Company Address : No. 285, Fenghua road, Luoyang, Henan, China.</p> <p>Postal code : 471000</p> <p>Phone :86-379-68611678</p> <p>Fax : 86-379-68611679</p> <p>E-mail: sales@jcb-bearing.com</p> <p>Reserved E-mail: sales@sphericalrollerbearing.net</p> <p>Website: www.jcb-bearing.com</p> <p>www.sphericalrollerbearing.net</p>	<h2>Spherical Roller Bearing</h2>		<h1>22310-E1-XL</h1>				
					Weight(kg)	Scale	
			S		1.9	—	
			Total page 5			Page No. 1	
<p>Luoyang JCB Bearing Technology Co., Ltd</p>							